

BIG BALE GRAPPLE

Available widths 54", 72", 84"
 Transport round bales, loose hay and other light materials.



73.4" JAW OPENING	2-CYL SINGLE-JAW GRAPPLE	> 2400 LB LOADER OPERATING CAP.
--------------------------------	---------------------------------------	---

- NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

MODEL	BG54	BG72	BG84
Overall Width (Inches)	56.0	74.0	86.0
Height: Overall / Bucket (Inches)	57.5 / 30.5		
Overall Depth (Inches)	40.8		
Number of Bucket Tines (with Sides)	3	5	6
Space Between Tines (Inches)	26.5	17.5	16.3
Bucket Tine Thickness (Inches)	0.5*		
Number of Grapple Tines	3	4	4
Space Between Grapple Tines (Inches)	20.0	19.3	19.3
Grapple Jaw Opening (Inches)	73.4		
Cylinder Bore / Stroke (Inches)	2.0 / 8.375		
Cylinder Pins / Hinge Pins Dia (Inches)	1.25 / 1.563		
Approximate Weight (Pounds)	900	1050	1150
Recommended loader capacity	Greater than 2400 pounds		
*Material is Grade 80 Plate (80,000 PSI Minimum Yield Strength).			

HAY BUCKET GRAPPLE

Available widths 72", 84"
 Haul hay bales, silage and other light materials.



74.3" JAW OPENING	2-CYL SINGLE-JAW GRAPPLE	> 2400 LB LOADER OPERATING CAP.
--------------------------------	---------------------------------------	---

1. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
2. 3/4" x 6" WELD-ON EDGE

MODEL	HBG72	HBG84
Width: Overall / Inside (Inches)	73.5 / 71.25	85.5 / 83.25
Height: Overall / Bucket (Inches)	58.3 / 31.4	
Overall Depth (Inches)	40.0	
Grapple Tine Thickness (Inches)	0.5*	
Number of Grapple Tines	4	
Space Between Grapple Tines (Inches)	19.3	
Grapple Jaw Opening (Inches)	74.3	
Bucket Capacity: Struck / Heaped (Cubic Feet)	27.7 / 33.2	32.2 / 38.8
Structural Wear Bars Under Bucket (1/2" x 4")	5	
Cylinder Bore / Stroke (Inches)	2.0 / 8.375	
Cylinder Pins / Hinge Pins Dia (Inches)	1.25 / 1.563	
Approximate Weight (Pounds)	1350	1450
Recommended loader capacity	Greater than 2400 pounds	
*Material is Grade 80 Plate (80,000 PSI Minimum Yield Strength).		