

# DOZER BLADE – 6 WAY

Available widths 72", 84", 96"

Heavy-duty frame, 3/8" thick moldboard and adjustable skid shoes.



**25.8"**  
BLADE  
HEIGHT

**1510-1640 LB**  
OVERALL WEIGHT  
(VARIES BY MODEL)

GREATER THAN  
**1800 LB**  
LOADER OPERATING CAPACITY

1. ANGLE THE BLADE 30° LEFT OR RIGHT & TILT 10° FROM INSIDE THE CAB

2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

3. 5/8" x 8" REVERSIBLE STEEL BOLT-ON EDGE

4. NOTE: Does not have a trip edge or trip moldboard.

MODEL	DZR72	DZR84	DZR96
Overall Width (Inches)	74.0	86.0	98.0
Height: Overall / Blade (Inches)		28.1 / 25.8	
Overall Depth (Inches)		38.0	
Blade Angle (Degrees)		(+/-) 30	
Width at Full Angle (Inches)	64.1	74.5	84.9
Blade Oscillation (Degrees)		(+/-) 10	
Moldboard Thickness (Inches)		0.375	
Cutting Edge (Inches)		5/8 x 8 Bolt-on	
Cylinder Bore / Stroke (Inches)		3.5 / 8.0	
Pins: Cylinder / Hinge / Oscillation (Inches)		1.563 / 2.125 / 2.125	
Approximate Weight (Pounds)	1510	1575	1640
Recommended Loader Capacity		Greater than 1800 pounds	