

HAY HANDLING, FORGED SPEARS

2000 LB
CAPACITY
ONE BALE MAXIMUM

· REPLACEABLE TAPERED FULLY FORGED STEEL SPEARS

FORGED ROUND BALE SPEAR // BSV48F



· 49" CONUS II FORGED MAIN SPEAR,
1 1/2" x 18" MACHINE POINTED STABILIZERS

FORGED BALE FORK // BFV48F



· 49" CONUS II FORGED SPEARS

FORGED ROUND/SQUARE BALE COMBO SPEAR // CBV48F



· 49" CONUS II FORGED MAIN SPEAR,
32" CONUS I FORGED STABILIZERS

FORGED SQUARE BALE SPEAR // SSV48F



· 32" CONUS I FORGED SPEARS

FORGED BIG SQUARE BALE SPEAR // BASS66F



· 32" CONUS I FORGED SPEARS

	MODEL	BSV48F	BFV48F	CBV48F	SSV48F	BASS66F
Overall Width (Inches)		45.5	45.5	45.5	45.5	66.5
Overall Height (Inches)				20.8		
Overall Depth (Inches)		54.6	52.7	47.7	35.8	47.8
Number of Main Spears		1	2	1	3	4
Main Spear Useable Length (Inches)		43.4	43.4	43.4	26.6	26.6
Number of Stabilizer Spears		2*	-	3	-	-
Stabilizer Spear Useable Length (Inches)		17.4	-	26.6	-	-
Bottom Spear Space (Inches)		36.0	-	20.9	-	18.9 / 20.5
Approximate Weight (Pounds)		210	235	235	205	260
Capacity, with Bale Against Frame (Pounds)				2000		

*Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).

Effective 01.01.22 - All information subject to change without notice. | 61