

HAY HANDLING, FORGED SPEARS

2000 LB
CAPACITY
ONE BALE MAXIMUM

REPLACEABLE TAPERED FULLY FORGED STEEL SPEARS

FORGED ROUND BALE SPEAR // BSV48F



49" CONUS II FORGED
MAIN SPEAR,
1 1/2" x 18" MACHINE
POINTED STABILIZERS

FORGED BALE FORK // BFV48F



49" CONUS II
FORGED SPEARS

FORGED ROUND/SQUARE BALE COMBO SPEAR // CBV48F



49" CONUS II FORGED
MAIN SPEAR,
32" CONUS I FORGED
STABILIZERS

FORGED SQUARE BALE SPEAR // SSV48F



32" CONUS I
FORGED SPEARS

FORGED BIG SQUARE BALE SPEAR // BASS66F



32" CONUS I
FORGED SPEARS

MODEL	BSV48F	BFV48F	CBV48F	SSV48F	BASS66F
Overall Width (in.)	45.5	45.5	45.5	45.5	66.5
Overall Height (in.)			20.8		
Overall Depth (in.)	54.6	52.7	47.7	35.8	47.8
Number of Main Spears	1	2	1	3	4
Main Spear Useable Length (in.)	43.4	43.4	43.4	26.6	26.6
Number of Stabilizer Spears	2 ¹	-	3	-	-
Stabilizer Spear Useable Length (in.)	17.4	-	26.6	-	-
Bottom Spear Space (in.)	36.0	36.0	20.9	-	18.9 / 20.5
Approximate Weight (lbs)	210	235	235	205	260
Capacity, with Bale Against Frame (lbs)			2000		

¹Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).