

## HAY HANDLING, MACHINE POINTED SPEARS

**2000 LB**  
CAPACITY  
ONE BALE MAXIMUM

• REPLACEABLE SPEARS MADE FROM 1045 CFSR ROUND STOCK

### ROUND BALE SPEAR // BSV48



• 2" x 48" MAIN SPEAR,  
1 1/2" x 18" STABILIZERS

### BALE FORK // BFV48



• 2" x 48" SPEARS

### ROUND/SQUARE BALE COMBO SPEAR // CBV48



• 1 3/4" x 42" MAIN SPEAR,  
1 3/4" x 30" STABILIZERS

### SQUARE BALE SPEAR // SSV48



• 1 3/4" x 42" MAIN SPEAR,  
1 3/4" x 30" STABILIZERS

### BIG SQUARE BALE SPEAR // BASS66



• 1 3/4" x 42" MAIN SPEARS,  
1 3/4" x 30" STABILIZERS

	MODEL	BSV48	BFV48	CBV48	SSV48	BASS66
Overall Width (Inches)		45.5	45.5	45.5	45.5	66.5
Overall Height (Inches)				20.8		
Overall Depth (Inches)		53.6	51.7	46.7	34.8	46.8
Number of Main Spears*		1	2	1	3	2
Main Spear Useable Length (Inches)		42.3	42.3	37.8	25.8	37.8
Number of Stabilizer Spears*		2	-	3	-	2
Stabilizer Spear Useable Length (Inches)		17.4	-	25.8	-	25.8
Bottom Spear Space (Inches)		-	36.0	20.9	-	-
Approximate Weight (Pounds)		230	270	260	225	310
Capacity, with Bale Against Frame (Pounds)				2000		

\*Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).