

# STUMP BUCKET

Remove stumps, roots and rocks.



1. COMPACT DEPTH MAXIMIZES LOADER BREAKOUT FORCE FOR REMOVING STUMPS
2. 3/4" x 6" WELD-ON EDGE WITH REPLACEABLE SERIES 23 TEETH (REPLACEMENT TEETH, PIN, & SHANK AVAILABLE)
3. BUCKET REINFORCED WITH LARGE GUSSET PLATES

MODEL	STMP
Overall Width (Inches)	45.6
Height: Overall / Bucket (Inches)	39.0 / 20.7
Overall Depth (Inches)	46.3
Shovel Width: Bottom / Top (In)	16.0 / 23.8
Space Between Teeth (Inches)	3.3
Shovel Depth (Inches)	29.6
Shovel Depth, With Teeth (In)	37.3
Approximate Weight (Pounds)	375
Recommended Loader Capacity	Greater than 1500 pounds

# STUMP BUCKET GRAPPLE

Remove and transport stumps, roots and rocks.



<b>39.0"</b> JAW OPENING	<b>1-CYL</b> SINGLE JAW GRAPPLE	<b>STANDARD WITH CYLINDER GUARD</b>
--------------------------------	---------------------------------------	---

1. COMPACT DEPTH MAXIMIZES LOADER BREAKOUT FORCE FOR REMOVING STUMPS
2. 3/4" x 6" WELD-ON EDGE WITH REPLACEABLE SERIES 23 TEETH (REPLACEMENT TEETH, PIN, & SHANK AVAILABLE)
3. BUCKET REINFORCED WITH LARGE GUSSET PLATES
4. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE

MODEL	STMPG
Overall Width (Inches)	45.6
Height: Overall / Bucket (Inches)	39.0 / 20.7
Overall Depth (Inches)	46.3
Shovel Width: Bottom / Top (In)	16.0 / 23.8
Space Between Teeth (Inches)	3.3
Shovel Depth (Inches)	29.6
Shovel Depth, With Teeth (In)	37.3
Grapple Jaw Opening (Inches)	39.0
Cylinder Bore / Stroke (Inches)	2.0 / 8.375
Cylinder Pins / Hinge Pins Dia (In)	1.25 / 1.563
Approximate Weight (Pounds)	590
Recommended Loader Capacity	Greater than 1500 pounds