TILLER

Available widths 54" & 72"

Offset design to cover tire tracks and till next to buildings, sidewalks, etc.

EATON
Char-Lynn

15-25 GPM RECOMMENDED FLOW RATE	DIRECT DRIVE EATON® MOTOR	GREATER THAN 1300 LB LOADER OPERATING CAPACITY

1. AGGRESSIVE DUAL-EDGE TINES FOR OPERATING IN FORWARD OR REVERSE
2. TILLER SHAFT SUPPORTED BY 2" DIAMETER BEARINGS ON EACH SIDE
3. BOLT-ON HEAT-TREATED TINES FOR MAX STRENGTH
4. GUARDED MOTOR ON BOTTOM & SIDES

MODEL	TLR54	TLR72
Working Width (in.)	54.0	72.0
Overall Width (in.)	70.5	88.5
Loader Width Coverage, Outside Tire (in.)	68.0	80.0
Overall Height (in.)	28.0	
Overall Depth (in.)	32.0	
Tilling Depth (in.)	6.0	
Working Offset (in.)	7.0[1]	4.0[1]
Drum Diameter (in.)	22.0	
Number of Tines (in.)	28	36
Recommended Flow Rate (GPM)	15-25 Standard Flow Only	
Approximate Weight (lbs)	900	1050
Recommended Loader Capacity	Greater than 1300 lbs	

[1]Distance between the center of the quick-tach plate and center of the working width.