

## U-BLADE

Available widths 26", 30", 36"  
Dual-point blade design for digging and trenching in forward and reverse.



**> 1500 LB  
LOADER  
OPERATING CAP.**

1. CARRY & TRANSPLANT TREES & ROCKS, DIG TRENCHES & BREAK UP COMPACTED SOIL
2. 3/8" THICK HIGH-CARBON STEEL BLADE

MODEL	UBV26	UBV30	UBV36
Inside Blade Diameter (Inches)	26.0	30.0	36.0
Overall Width (Inches)	45.6		
Height: Overall / Blade, With Sides (Inches)	38.0 / 17.5	43.5 / 22.5	41.0 / 19.5
Overall Length (Inches)	46.8		
Approximate Digging Depth (Inches)	48.0*		
Approximate Weight (Pounds)	370	390	390
Recommended Loader Capacity	Greater than 1500 pounds		

\*Digging depth varies with size and brand of machine.

## TILLER

Available widths 54", 72"  
Offset design to cover tire tracks and till next to buildings, sidewalks, etc.



**FAT·N**  
Char-Lynn

**15-25 GPM  
RECOMMENDED  
FLOW RATE** | **DIRECT DRIVE MOTOR  
WITH RELIEF  
VALVE PROTECTION** | **> 1300 LB  
LOADER  
OPERATING CAP.**

1. AGGRESSIVE DUAL-EDGE TINES FOR OPERATING IN FORWARD OR REVERSE
2. TILLER SHAFT SUPPORTED BY 2" DIAMETER BEARINGS ON EACH SIDE
3. BOLT-ON HEAT-TREATED TINES FOR MAX STRENGTH
4. GUARDED MOTOR ON BOTTOM & SIDES

MODEL	TLR54	TLR72
Working Width (Inches)	54.0	72.0
Overall Width (Inches)	70.5	88.5
Loader Width Coverage, Outside Tire (Inches)	68.0	80.0
Overall Height (Inches)	28.0	
Overall Depth (Inches)	32.0	
Tilling Depth (Inches)	6.0	
Working Offset (Inches)	7.0*	4.0*
Drum Diameter (Inches)	22.0	
Number of Tines (Inches)	28	36
Recommended Flow Rate (GPM)	15-25 Standard Flow Only	
Approximate Weight (Pounds)	900	1050
Recommended Loader Capacity	Greater than 1300 pounds	

\*Distance between the center of the quick-tach plate and center of the working width.

