

V20 MINI SKID STEER SCRAP GRAPPLE

Available widths 36", 42" & 48"

Solid bottom grapple for scooping and hauling loose and bulky debris.



30.9" JAW OPENING	1-CYL SINGLE JAW GRAPPLE	> 500 LB LOADER OPERATING CAP.
-------------------------	--------------------------------	--------------------------------------

1. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE
2. 1/2" x 4" WELD-ON EDGE
3. STANDARD WITH CYLINDER GUARD

CHOOSE MINI SKID MOUNT:
 · TORO®/MINI UNIVERSAL
 · BOBCAT®
 · ASV®
 · Universal skid steer quick tach mount not available.



ADDITIONAL
EDGE OPTION:
STANDARD BOLT-ON

MODEL	CSG36	CSG42	CSG48
Overall Width (in.)	36.0	42.0	48.0
Height: Overall / Bucket (in.)	27.0 / 24.5		
Overall Depth (in.)	30.8		
Cylinder Bore / Stroke (in.)	2.0 / 6.0		
Cylinder Pins / Hinge Pins Dia. (in.)	1.0 / 1.0		
Grapple Jaw Opening (in.)	30.9		
Approximate Weight (lbs)	325*	355*	380*
Recommended Loader Capacity	Greater than 500 lbs		

*Bobcat® mount adds approximately 10 lbs to model weight.

V20 MINI SKID STEER ROOT RAKE GRAPPLE

Available widths 36", 42" & 48"

Quickly dig, rake, pile, and load brush. Designed light but tough for mini skid steers.



0.375" AR400 STEEL TINES	32.2" JAW OPENING	21.5" OVERALL DEPTH	> 500 LB LOADER OPERATING CAP.
-----------------------------	-------------------------	---------------------------	--------------------------------------

1. TWO-CYLINDER SINGLE JAW GRAPPLE
2. EVERY TINE IS MADE FROM ONE PIECE OF STEEL FOR MAXIMUM RIGIDITY
3. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

CHOOSE MINI SKID MOUNT:
 · TORO®/MINI UNIVERSAL
 · BOBCAT®
 · ASV®
 · Universal skid steer quick tach mount not available.

MODEL	CRG36	CRG42	CRG48
Overall Width (in.)	35.8	43.8	51.8
Height: Overall / Bucket (in.)	24.7 / 23.6		
Overall Depth (in.)	21.5		
Number of Tines (w/ sides)	6	7	8
Space Between Tines / Grapple Jaws (in.)	6.8 / 7.2	7.0 / 7.3	7.1 / 7.4
Tine Thickness (in.)	0.375*		
Cylinder Bore / Stroke (in.)	2.0 / 6.0		
Cylinder Pins / Hinge Pins Dia. (in.)	1.0 / 1.0		
Grapple Jaw Opening (in.)	32.2		
Approximate Weight (lbs)	270	300	335**
Recommended Loader Capacity	Greater than 500 lbs		

*Material is AR400 Plate (150,000 PSI Minimum Yield Strength).

**ASV® mount adds approximately 35 lbs and Bobcat® mount adds 20 lbs to model weight.