

V30 CT RAIL PALLET FORK

Adjustable ITA Class II forged tines.



45.5" FRAME WIDTH	2200 LB CAPACITY	42" TINE LENGTH	< 1500 LB LOADER OPERATING CAP.
-------------------------	---------------------	-----------------------	---------------------------------------

1. 3/4" BEVELED RAIL & 3/16" BACKREST
2. BRICKREST FLUSH WITH TINES TO HELP STABILIZE LOADS
3. BRACING CENTERED ON QUICK TACH FOR EASY HOOKUP

MODEL	PF4222-CT
Height: Overall w/Step / Frame (Inches)	50.5 / 45.5
Overall Height (Inches)	29.7
Tine: Length / Width / Thickness (Inches)	42.0 / 3.0 / 1.19
Tine Space: Min / Max (Inches)	8.9 / 40.9
Approximate Weight (Pounds)	265
Capacity (Pounds)	2200
Recommended Loader Capacity	Less than 1500 pounds

V30 CT SKELETON ROCK BUCKET

Available widths 48", 54", 60", 66", 72"

Pick up rocks and leave dirt behind.

0.25" GRADE 50 STEEL TINES	3.1" TINE SPACING	29.0" DEPTH	19.9" HEIGHT	< 1500 LB LOADER OPERATING CAP.
-------------------------------	-------------------------	----------------	-----------------	---------------------------------------



1. EVERY TINE IS MADE FROM ONE PIECE STEEL FOR MAXIMUM RIGIDITY
2. ROCK DAM & NOTCH NEAR TINE TIPS HOLD ROCKS SECURELY

MODEL	SRV48-CT	SRV54-CT	SRV60-CT	SRV66-CT	SRV72-CT
Width: Overall / Inside (Inches)	50.9 / 46.3	54.3 / 52.6	60.9 / 59.3	67.5 / 65.9	74.1 / 72.5
Overall Height (Inches)	19.9				
Depth: Overall / Inside (Inches)	29.0 / 23.5				
Number of Tines (w/ Sides)	15	17	19	21	23
Space Between Tines (In)	3.1				
Tine Thickness (Inches)	0.25*				
Side Plate Thickness (Inches)	0.375*				
Approximate Weight (Pounds)	210	230	250	270	290
Recommended Loader Capacity	Less than 1500 pounds				

*Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).