

# REDESIGNED V30 CT ROOT RAKE GRAPPLE

54" · 60" · 66"

Universal skid steer mount only.

 **0.25" AR400 STEEL TINES**

**35.5"**  
JAW OPENING

**16.6"**  
OVERALL DEPTH

LESS THAN **1500LB**  
LOADER OPERATING CAPACITY



**SINGLE JAW DESIGN**  
Back-drag to rake brush and material into piles for easy hauling.

**HIGH STRENGTH STEEL**  
Every tine constructed from AR400 steel.

**PREMIUM COMPONENTS**  
NitroSteel® cylinder rods and Teflon® coated bushings on all pivots.



**TINE GUSSETS**  
URG60 and URG66 tines are gusseted for extra strength. URG54 tines are not gusseted.



MODEL	URG54-CT	URG60-CT	URG66-CT
Overall Width (Inches)	56.5	61.5	67.5
Height: Overall / Bucket (Inches)		27.9 / 24.9	
Overall Depth (Inches)		16.6	
Number of Bottom Tines	7	8	9
Space Between Tines: Bottom (Inches)	4.8 / 10.5	4.8 / 9.8	4.8 / 9.1
Space Between Tines: Grapple Jaws (In)	7.8 / 11.2	7.3 / 9.8	7.0 / 9.2
Tine Thickness (Inches)		0.25*	
Cylinder Bore / Stroke (Inches)		2.0 / 6.0	
Cylinder Pins / Hinge Pins Diameter (In)		1.0	
Approximate Weight (Pounds)	255	300	320
Recommended Loader Capacity	Less than 1500 pounds		

\*Material is AR400 Plate (150,000 PSI Minimum Yield Strength).