

V30 CT SKELETON GRAPPLE

Available widths 48", 54", 60", 66", 72"

Open-sided design for hauling brush and logs. Open bottom allows dirt to fall through.



V30 CT SKELETON ROCK GRAPPLE

Available widths 48", 54", 60", 66", 72"

Quickly dig, rake, pile and load brush. Designed light but tough for compact tractors.



0.25" GRADE 50
STEEL TINES

28.7"
JAW
OPENING

2-CYL
INDEPENDENT
GRAPPLE

LESS THAN
1500 LB
LOADER OPERATING CAPACITY

1. EVERY TINE IS MADE FROM ONE PIECE OF 1/4" GRADE 50 STEEL FOR MAXIMUM RIGIDITY
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE
3. SRGV-CT: CURVED SIDE PLATE TO ALLOW WIDE MATERIAL HANDLING
4. SRGV-CT: ROCK DAM & NOTCH NEAR TINE TIPS HOLD ROCKS SECURELY
5. SRGV-CT: TINES FULLY GUSSETED FOR ADDED STRENGTH



OPTION: CYLINDER GUARDS
Pair, installed.

MODEL	SGV48-CT SRGV48-CT	SGV54-CT SRGV54-CT	SGV60-CT SRGV60-CT	SGV66-CT SRGV66-CT	SGV72-CT SRGV72-CT
Overall Width (Inches)	47.9	54.3	60.9	67.5	74.1
Height: Overall / Bucket (Inches)			22.9 / 19.0		
Depth: Overall / Inside (Inches)			29.0 / 23.5		
Number of Tines (with Sides)	8 15	9 17	10 19	11 21	12 23
Space Between Tines (Inches)			6.4 3.1		
Tine Thickness (Inches)			0.25*		
Side Plate Thickness (Inches)			0.375*		
Cylinder Bore / Stroke (Inches)			2.0 / 6.0		
Cylinder Pins / Hinge Pins Dia (In)			1.0		
Grapple Jaw Opening (Inches)			28.7		
Approximate Weight (Pounds)	290 345	305 365	320 385	335 405	350 425
Recommended Loader Capacity	Less than 1500 pounds				

*Material is Grade 50 Plate (50,000 PSI Minimum Yield Strength).