

V40 SNOW / LIGHT MATERIAL BUCKET

60" · 66" · 72" · 78" · 84" · 96"

37.6"
DEPTH

26.6"
HEIGHT

UP TO **29CUFT**
STRUCK CAPACITY
(VARIES BY MODEL)

UP TO **35CUFT**
HEAPED CAPACITY
(VARIES BY MODEL)

LESS THAN **2400LB**
LOADER OPERATING CAPACITY



- > High capacity design allows large volumes of snow, mulch or other light materials to be hauled per load.
- > 3/16" thick shell and side plates.
- > 3/8" thick side edges and gussets for extra durability.
- > 3/4" x 6" weld-on edge with holes to accept optional edges.

NOTE: SLHV96 has two 3/8" thick vertical braces inside bucket. Similar to the V50 Snow Bucket.

EDGE OPTIONS



BOLT-ON



SERRATED

MODEL	SLHV60	SLHV66	SLHV72	SLHV78	SLHV84	SLHV96
Width: Overall / Inside (In)	61.5/59.3	67.5/65.3	73.5/71.3	79.5/77.3	85.5/83.3	97.5/95.3
Overall Height (Inches)	26.6					
Depth: Overall / Inside (In)	37.6 / 36.8					
Bucket Capacity: Struck / Heaped (Cu. Ft.)	18.6/22.3	20.4/24.5	22.2/26.6	24.0/28.8	25.8/31.0	29.4/35.3
Bucket Back Angle (Degrees)	66					
Shell Thickness (Inches)	0.19					
Side Plate Thickness (Inches)	0.19					
Structural Wear Bars Under Bucket (1/2" x 4")	2	2	2	3	3	4
Approximate Weight (Pounds)	500	535	570	605	640	770
Recommended Loader Capacity	Less than 2400 pounds					

V50 SNOW / LIGHT MATERIAL BUCKET

72" · 78" · 84" · 96" · 101"

40.6"
DEPTH

29.8"
HEIGHT

UP TO **37CUFT**
STRUCK CAPACITY
(VARIES BY MODEL)

UP TO **44CUFT**
HEAPED CAPACITY
(VARIES BY MODEL)

GREATER THAN **1800LB**
LOADER OPERATING CAPACITY



- > High capacity design allows large volumes of snow, mulch or other light materials to be hauled per load.
- > 3/16" thick shell and 1/4" side plates.
- > Two, 3/8" thick vertical braces inside bucket to increase rigidity.
- > 3/8" thick side edges and gussets for extra durability.
- > 8" tall windows cut into the back to increase operator visibility. Available with solid back as special order.
- > 3/4" x 6" weld-on edge with holes to accept optional edges.

EDGE OPTIONS



BOLT-ON



SERRATED

MODEL	MSHV72	MSHV78	MSHV84	MSHV96	MSHV101
Width: Overall / Inside (In)	73.5/71.3	79.5/77.3	85.5/83.3	97.5/95.3	101.5/99.3
Overall Height (Inches)	29.8				
Depth: Overall / Inside (In)	40.6 / 39.9				
Window Height (Inches)	8.0				
Bucket Capacity: Struck / Heaped (Cu. Ft.)	26.6 / 31.9	28.8 / 34.6	31.0 / 37.2	35.5 / 42.6	37.0 / 44.5
Bucket Back Angle (Degrees)	66				
Shell Thickness (Inches)	0.19				
Side Plate Thickness (Inches)	0.25				
Structural Wear Bars Under Bucket (1/2" x 4")	3	5	5	5	5
Approximate Weight (Pounds)	660	730	765	830	850
Recommended Loader Capacity	Greater than 1800 pounds				