

V40 UTILITY FORK GRAPPLE

Available widths 60", 66", 72", 78"

Single jaw grapple designed to handle manure, brush and debris.



1.75" 1045 CSFR STEEL TINES

38.0" JAW OPENING

~5.4" TINE SPACING

< 2400 LB LOADER OPERATING CAP.

1. NO CROSS MEMBER FOR BETTER PENETRATION
2. HIGH STRENGTH REPLACEABLE TINES
3. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON HINGE

	MODEL MGV160	MGV166	MGV172	MGV178
Overall Width (Inches)	61.3	67.3	73.3	79.3
Height: Overall / Bucket (In)	27.6 / 21.5			
Overall Depth (Inches)	33.5			
Number of Tines (w/ Sides)	9	10	11	12
Space Between Tines (In)	5.4	5.3	5.2	5.1
Tine Diameter (Inches)	1.75*			
Cylinder Bore / Stroke (In)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia (In)	1.25 / 1.25			
Grapple Jaw Opening (Inches)	38.0			
Approximate Weight (Pounds)	835	860	950	990
Recommended Loader Capacity	Less than 2400 pounds			

*Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).

V50 TINE FORK GRAPPLE

Available widths 60", 66", 72", 78"

High strength design for handling manure, brush and debris.



2.0" 1045 CSFR STEEL TINES

38.2" JAW OPENING

~5.0" TINE SPACING

< 2400 LB LOADER OPERATING CAP.

1. NO CROSS MEMBER FOR BETTER PENETRATION
2. 1/2" VERTICAL BRACES INSIDE BUCKET
3. HIGH STRENGTH REPLACEABLE TINES
4. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS

	MODEL TBG260	TBG266	TBG272	TBG278
Overall Width (Inches)	61.3	67.3	73.3	79.3
Height: Overall / Bucket (Inches)	28.5 / 21.8			
Overall Depth (Inches)	37.0			
Number of Tines (w/ Sides)	9	10	11	12
Space Between Tines (Inches)	5.1	5.0	4.9	4.8
Tine Diameter (Inches)	2.0*			
Cylinder Bore / Stroke (Inches)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia (In)	1.25 / 1.563			
Grapple Jaw Opening (Inches)	38.2			
Approximate Weight (Pounds)	1040	1110	1180	1250
Recommended Loader Capacity	Less than 2400 pounds			

*Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).