

V40 UTILITY FORK

Available widths 60", 66", 72", 78"

A cost effective solution for transporting semi-loose material.



1.75" 1045 CSFR
STEEL TINES

~5.4"
TINE
SPACING

< 2400 LB
LOADER
OPERATING CAP.

1. NO CROSS MEMBER FOR BETTER PENETRATION

2. HIGH STRENGTH REPLACEABLE TINES

| | MODEL | MV60 | MV66 | MV72 | MV78 |
|-----------------------------|-------|------|------|-----------------------|------|
| Overall Width (Inches) | | 61.3 | 67.3 | 73.3 | 79.3 |
| Overall Height (Inches) | | | | 21.5 | |
| Overall Depth (Inches) | | | | 33.5 | |
| Number of Tines (w/ Sides) | | 9 | 10 | 11 | 12 |
| Space Between Tines (In) | | 5.4 | 5.3 | 5.2 | 5.1 |
| Tine Diameter (Inches) | | | | 1.75* | |
| Approximate Weight (Pounds) | | 545 | 570 | 655 | 695 |
| Recommended Loader Capacity | | | | Less than 2400 pounds | |

*Material is 1045 CFSR Round Stock (100,000 PSI Minimum Yield Strength).

MANURE SLURRY BUCKET

Available widths 66", 72", 78", 84"



37.0"
DEPTH

25.3"
HEIGHT

UP TO
21CU FT
STRUCK CAP.

UP TO
25CU FT
HEAPED CAP.

> 1500 LB
LOADER
OPERATING CAP.

1. 60° BACK ANGLE & TOP FORMED PROFILE TO LIMIT SPILLAGE

2. CURVED INSIDE FOR EASIER CLEAN OUT

3. 3/4" x 6" WELD-ON EDGE WITH HOLES FOR OPTIONAL EDGES

4. REVERSIBLE BOLT-ON SIDE WEAR EDGES



| | MODEL | MSB66 | MSB72 | MSB78 | MSB84 |
|---|-------|-------------|-------------|--------------------------|-------------|
| Width: Overall / Inside (Inches) | | 68.3 / 65.3 | 74.3 / 71.3 | 80.3 / 77.3 | 86.3 / 83.3 |
| Overall Height (Inches) | | | | 25.3 | |
| Depth: Overall / Inside (Inches) | | | | 37.0 / 32.6 | |
| Bucket Capacity: Struck / Heaped (Cubic Feet) | | 16.9 / 20.3 | 18.4 / 22.1 | 20.0 / 24.0 | 21.5 / 25.8 |
| Structural Wear Bars Under Bucket (1/2" x 4") | | 3 | 3 | 4 | 4 |
| Approximate Weight (Pounds) | | 600 | 710 | 770 | 810 |
| Recommended Loader Capacity | | | | Greater than 1500 pounds | |