

V50 SCRAP GRAPPLE

Available widths 60", 66", 72", 78"


Solid bottom grapple for scooping and hauling loose and bulky debris.

36.9" JAW OPENING	2-CYL INDEPENDENT GRAPPLE	< 2400 LB LOADER OPERATING CAP.
--------------------------------	--	---

1. 1/2" VERTICAL BRACES INSIDE BUCKET
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. 3/4" x 6" WELD-ON EDGE
4. STANDARD WITH CYLINDER GUARDS



**ADDITIONAL
EDGE OPTIONS**
See page 81



**STANDARD
BOLT-ON**



**SERRATED
BOLT-ON**

	MODEL SBG60	SBG66	SBG72	SBG78
Overall Width (Inches)	61.5	67.5	73.5	79.5
Height: Overall / Bucket (Inches)	27.3 / 20.8			
Overall Depth (Inches)	35.5			
Structural Wear Bars Under Bucket (1/2" x 4")	2	2	2	3
Cylinder Bore / Stroke (Inches)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia (In)	1.25 / 1.563			
Grapple Jaw Opening (Inches)	36.9			
Approximate Weight (Pounds)	895	930	965	1015
Recommended Loader Capacity	Less than 2400 pounds			

V60 SCRAP GRAPPLE

Available widths 72", 78", 84", 90"

The toughest solid bottom grapple for scooping and hauling loose and bulky debris.

38.8" JAW OPENING	2-CYL INDEPENDENT GRAPPLE	> 2400 LB LOADER OPERATING CAP.
--------------------------------	--	---

1. EXTRA BRACE PLATE & 1/2" VERTICAL BRACES INSIDE BUCKET FOR ADDED STRENGTH
2. NITROSTEEL® CYLINDER RODS & TEFLON® COATED BUSHINGS ON ALL PIVOTS
3. 3/4" x 6" WELD-ON EDGE
4. STANDARD WITH CYLINDER GUARDS



**ADDITIONAL
EDGE OPTIONS**
See page 81



**STANDARD
BOLT-ON**



**SERRATED
BOLT-ON**

	MODEL ISG72	ISG78	ISG84	ISG90
Overall Width (Inches)	73.5	79.5	85.5	91.5
Height: Overall / Bucket (Inches)	29.0 / 22.5			
Overall Depth (Inches)	35.5			
Structural Wear Bars Under Bucket (1/2" x 4")	4	5	5	5
Cylinder Bore / Stroke (Inches)	2.0 / 8.375			
Cylinder Pins / Hinge Pins Dia (In)	1.25 / 1.563			
Grapple Jaw Opening (Inches)	38.8			
Approximate Weight (Pounds)	1080	1130	1170	1210
Recommended Loader Capacity	Greater than 2400 pounds			