



V50 LOW PROFILE DIRT BUCKET

60" · 66" · 72" · 78" · 84"




Cross Section



STANDARD BRACING

- > Low profile and extended bottom for better visibility of cutting edge.
- > ¾" x 6" weld-on cutting edge with holes to accept optional edges.

GRADING BEND WITH ROLLED INSIDE




Cross Section



- > Permits better grading in reverse than standard profile buckets.
- > **Grading Bend** Buckets come with Rolled Inside.
- > **Rolled Inside** makes clean out easier than a standard profile bucket.

OPTION: SIDE CUTTERS



- > Reversible – only one in the industry.
- > Improves performance in hard, compacted soils.
- > Cast steel lengthens life of bucket sides.
- > Not compatible with Toothbars.

	MODEL DHV60EX-GB	DHV66EX-GB	DHV72EX-GB	DHV78EX-GB	DHV84EX-GB
Width: Overall Inside (Inches)	61.5 59.3	67.5 65.3	73.5 71.3	79.5 77.3	85.5 83.3
Overall Height (Inches)	20.5				
Depth: Overall Inside (Inches)	33.0 28.6				
Bucket Capacity: Struck Heaped (Cu. Ft.)	11.9 14.3	13.1 15.7	14.4 17.3	15.7 18.8	17.0 20.4
Bucket Back Angle (Degrees)	66				
Shell Thickness (Inches)	0.19				
Side Plate Thickness (Inches)	0.25				
Structural Wear Bars Under Bucket (½"x 4")	2	2	2	3	3
Approximate Weight (Pounds)	490	525	555	600	635
Recommended Loader Capacity	Less than 2400 pounds				

