

V60 MULTI-PURPOSE BUCKET (4-IN-1)


66" · 72" · 78" · 84"



- > Multiple functions in one attachment to save time and money including dozing, clamming, leveling, and bottom dumping.
- > Guarded two-cylinder design.
- > NitroSteel[®] cylinder rods and Teflon[®] coated bushings on all pivots.
- > 5/8" x 6" reversible, replaceable bolt-on edge at rear of clam and front of dozer.
- > 1/4" shell, additional bracing, 1/2" hinge structure and reinforcement at rear corners of dozer and quick-tach plate.
- > 1" x 6" weld-on cutting edge with holes to accept optional edges.



OPTION: HOLDING VALVE



- > Increases holding force of hydraulic cylinders.

OPTION: SIDE CUTTERS



REVERSIBLE

- > Improves performance in hard, compacted soils.

EDGE OPTIONS



BOLT-ON



SERRATED



**WELD - ON
TEETH**

	MODEL	HMPV66	HMPV72	HMPV78	HMPV84
Width: Overall / Inside (Inches)		67.5 / 65.5	73.5 / 71.5	79.5 / 77.5	85.5 / 83.5
Height: Overall / Bucket / Open (Inches)		29.8 / 21.3 / 46.0			
Depth: Overall / Inside (Inches)		37.0 / 28.5			
Dozer Width (Inches)		65.9	71.9	77.9	83.9
Clam Opening (Inches)		33.0			
Thickness: Shell / Hinge Structure (Inches)		0.25 / 0.5			
Structural Wear Bars Under Bucket (1/2" x 4")		4	4	5	5
Cylinder Bore / Stroke (Inches)		2.5 / 8.375			
Cylinder Pins / Hinge Pins Diameter (Inches)		1.25 / 1.563			
Approximate Weight (Pounds)		1045	1100	1165	1220
Recommended Loader Capacity		Greater than 2400 pounds			