

## V60 ROOT RAKE GRAPPLE

Available widths 72", 78" & 84"

The toughest and largest Virnig root rake designed to dig, rake, pile, and load brush.



Known clearance issue with 72" RRG on Takeuchi® TL12.  
Known clearance issue with John Deere® 330G, 331G, 332G, 333G. No issues on other width RRGs.

<b>0.5" GRADE 80</b> STEEL TINES	<b>53.7"</b> JAW OPENING	<b>31.6"</b> OVERALL DEPTH	<b>2-CYL</b> SINGLE-JAW GRAPPLE	<b>GREATER THAN</b> <b>2200 LB</b> LOADER OPERATING CAPACITY
-------------------------------------	--------------------------------	----------------------------------	---------------------------------------	--

1. HARD STOPS PREVENT EXCESS CYLINDER STRESS
2. SERIES 23 PIN-ON TEETH CUT INTO SOIL, DIG OUT ROCKS & ROOTS (REPLACEMENT AVAILABLE)
3. STANDARD WITH CYLINDER GUARDS



	MODEL RRG72	RRG78	RRG84
Overall Width (in.)	74.5	80.5	86.5
Height: Overall / Bucket (in.)	38.3 / 29.7		
Overall Depth (in.)	31.6		
Number of Teeth	7	7	8
Space Between Teeth (in.)	9.8	10.8	9.8
Space Between Tines, Grapple Jaws (in.)	10.5	11.7	10.7
Tine Thickness (in.)	0.5*		
Cylinder Bore / Stroke (in.)	2.5 / 8.375		
Cylinder Pins / Hinge Pins Dia. (in.)	1.25 / 1.563		
Grapple Jaw Opening (in.)	53.7		
Approximate Weight (lbs)	1175	1230	1315
Recommended Loader Capacity	Greater than 2400 lbs		

\*Material is Grade 80 Plate (80,000 PSI Minimum Yield Strength).