

WIDE RAIL PALLET FORKS

Wider rail for better stability and adjustable ITA Class II forged tines.

54.5"
FRAME WIDTH

UP TO
6200 LB
CAPACITY
(VARIES BY MODEL)

42" TO 60"
TINE LENGTHS

1. 3/4" BEVELED RAIL
2. BRICKGUARD FLUSH WITH TINES TO HELP STABILIZE LOADS
3. BRACING CENTERED ON QUICK TACH FOR EASY HOOKUP
4. BOLT-ON STEP INSTALLS ON EITHER SIDE

WIDE RAIL PALLET FORK - HI-VIS



- REMOVE CENTER SECTION TO CHANGE TO A WALK-THROUGH BRICKGUARD
- 1/4" HIGH VISIBILITY BRICKGUARD

WIDE RAIL PALLET FORK - WALK-THROUGH



- WALK-THROUGH DESIGN ALLOWS QUICK CAB ACCESS
- 1/4" HIGH VISIBILITY BRICKGUARD

WIDE RAIL PALLET FORK - HEX-GUARD



- 3/16" CLASSIC VIRNIG BRICKGUARD

MODEL	W4240	W4840	W4255	W4855	W6055	W4862
Width: Overall w/Step / Frame (Inches)	59.5 / 54.5					
Overall Height (Inches)	37.0					
Tine: Length / Width / Thickness (Inches)	42.0/4.0/1.375	48.0/4.0/1.375	42.0/4.0/1.5	48.0/4.0/1.5	60.0/4.0/1.5	48.0/4.0/1.75
Tine Space: Min / Max (Inches)	8.8 / 49.1					
Approximate Weight (Pounds)	415*	435*	435*	450*	485*	465*
Capacity (Pounds)	4000	4000	5500	5500	5500	6200
Recommended Loader Capacity	< 2400	< 2400	< 2400	< 2400	> 2400	> 2400

*WPF model weights listed. Subtract 15 pounds for WPFWT model weights. Subtract 25 pounds for WPFHG model weights.